

CLASSIC



Over five decades Spondor Classic loudspeakers have earned iconic status as the reference standard for many audiophiles, musicians and professional sound engineers. Inspired by the enthusiastic world-wide response following the introduction of our flagship Spondor SP200, in 2022 we introduced the most significant performance improvements ever across all models.

Our latest models are built around a totally new generation of Spondor drive units. Featuring advanced polymer and Kevlar cones, cast magnesium alloy chassis, high-efficiency motor systems, optimised electro-dynamic damping and excellent thermal dissipation, they deliver a truly captivating sound with unprecedented transparency and dynamic contrast.

With meticulously refined crossover networks, enhanced cabinet structures, new elastomer panel damping and new style magnetic grilles, the new Spondor Classic loudspeakers deliver music with the captivating warmth and charm of the 70s originals. Refined and perfected over five decades, Spondor Classic offers the ultimate in pure listening pleasure for serious audiophiles.

SPENDOR

MADE FOR MUSIC. DESIGNED FOR YOU.

TECHNICAL SPECIFICATION

- New Spendor EP77 polymer cone drive units
- Bass drivers with Kevlar composite stabiliser domes
- New cabinet design with magnetic grille
- Three finishes - Walnut, Cherry & Walnut Ti *for 100 & 200
- Calibrated and matched to broadcast reference standard
- Dedicated high performance stand available
- Designed and Manufactured in the UK



MODEL	Classic 4/5	Classic 3/1	Classic 2/3	Classic 1/2	Classic 100 & 100 Ti*	Classic 200 & 200 Ti*
DESCRIPTION	2-way sealed shelf mount	2-way reflex stand mount	2-way reflex stand mount	3-way reflex stand mount	3-way reflex stand mount	3-way sealed floorstanding
DRIVE UNITS	LF 15cm, HF 22mm	LF 18cm, HF 22mm	LF 22cm, HF 22mm	LF 22cm, MF 15cm, HF 22mm	LF 31cm, MF 18cm, HF 22mm	2xLF 31cm, MF 18cm, HF 22mm
H x W x D	308 x 188 x 165mm	395 x 220 x 285mm	543 x 273 x 338mm	621 x 308 x 374mm	700 x 370 x 433mm	1117 x 368 x 513mm
WEIGHT	5kg	9.9kg	14.5kg	22.6kg	36kg	55kg
RESPONSE	55Hz - 25kHz	40Hz - 25kHz	35Hz - 25kHz	30Hz - 25kHz	25Hz - 25kHz	20Hz - 25kHz
IMPEDANCE	8 ohms (min 6.6)	8 ohms (min 5.9)	8 ohms (min 6.8)	8 ohms (min 4.0)	8 ohms (min 4.7)	8 ohms (min 6.0)
AMPLIFIER	25-100 watts	25-150 watts	25-200 watts	25-200 watts	25-250 watts	25-300 watts
SENSITIVITY	84dB	88dB	88dB	87dB	89dB	89dB
CROSSOVER	4.2kHz	3.7kHz	3.6kHz	415Hz, 2.7kHz	490Hz, 3.6kHz	550Hz, 3.8kHz

SPENDOR

Spendor Audio Systems Ltd, G5 Ropemaker Park, South Road, Hailsham, East Sussex BN27 3GY UK
+44 (0)1323 843474 info@spendoraudio.com spendoraudio.com