



PRODUCT DATA SHEET CLASSIC 100Ti



The Classic 100Ti delivers a truly captivating full-scale sound with unprecedented transparency and dynamic contrast. Efficient and easy to drive. Equally at home with tube or solid-state electronics, analogue or digital sources, it always delivers consistent enjoyable sound.

## **HIGHLIGHTS**

- The Classic 100Ti walnut cabinet features (like all Spendor Classic models) Spendor Dynamic Damping technology. These panels are attached to a rigid front baffle finished in brushed titanium.
- The Classic 100Ti is built around two proprietary Spendor drive units. The 31cm woofer has a rigid, lightweight Kevlar-composite cone whilst the dedicated 18cm midrange unit features an EP77 polymer cone for ultra-low colouration. Both combine high efficiency motor systems and a magnesium alloy chassis into their designs.
- Use on the dedicated Spendor Classic 100 Stand for best results.
- Designed and Manufactured in the UK

## **TECHNICAL SPECIFICATION**

Description	3-way stand mount loudspeaker
Enclosure type	Twin port reflex loaded
Input connection	Three pairs gold plated precision binding posts
Typical in-room response	25Hz – 25kHz
Power handling	200 watts unclipped programme
Amplifier	25-250 watts
Sensitivity	89dB for 1 watt at 1 metre
Nominal impedance	8 ohms (min 4.7)
HF driver	22mm polyamide dome
MF driver	18cm EP77 polymer cone midrange unit
LF driver	31cm Kevlar <sup>©</sup> composite bass driver with Kevlar <sup>©</sup> composite stabilizer disc.
Crossover frequency	490Hz, 3.6kHz
Net Weight	36kg
Height	700mm
Width	370mm
Depth	433mm
Finishes	Walnut with Titanium faceplate
Included	Magnetic grille
Recommended stand	Dedicated Spendor Classic 100 Stand (not supplied)



Walnut

